



* OPTIONS :

1. MAY BE SUPPLIED WITH FILTER COVERING ENTIRE PACKAGE.
2. MAY BE SUPPLIED AS SHOWN WITH AN APERTURED LID WITH OR WITHOUT AN INTERNAL FILTER.

NOTES:

1. FILTER THICKNESS DEPENDENT ON TYPE. THIS MODEL ACCOMMODATES INTERNAL FILTERS .010 MIN TO .105 MAX THICK.
2. OBSERVE PRECAUTIONS FOR HANDLING ELECTROSTATIC SENSITIVE DEVICES.

| | | | | | |
|--|------|---------|--|-------------|-------------|
| F | N/A | 8-03-05 | ADDED NOTE 2 | RD | DD |
| E | 1176 | 5-19-98 | UPDATE PIN OUT | RD | DD |
| REV | ECN | DATE | DESCRIPTION | | |
| Distribution and Technical Support: Silverlight Ltd., Switzerland info@silverlight.ch www.silverlight.ch | | | MODEL 420M8 SINGLE ELEMENT IR DETECTOR WITH HEAT SINK | | |
| | RD | 1-16-91 | Λ | | REV. |
| | DD | 2-4-91 | 7800444 | | F |
| | LC | 2-5-91 | /800444F.CKD | SCALE : 3/1 | SHEET 1 L 1 |

NOTICE: ELTEC INSTRUMENTS, INC. CLAIMS PROPRIETARY RIGHTS IN THE INFORMATION DISCLOSED ON THIS DRAWING. IT IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT, IN WHOLE OR IN PART, BE USED TO MANUFACTURE ANYTHING WHETHER OR NOT SHOWN HEREON, REPRODUCED OR DISCLOSED TO ANYONE WITHOUT DIRECT WRITTEN PERMISSION FROM ELTEC INSTRUMENTS, INC.